



## DANE TECHNICZNE

model wentylatora	wydajność max	ciśnienie max	prędkość obrotowa	napięcie nominalne	natężenie znamionowe**	pobór mocy max	poziom ciśnienia akust.*	temp. pracy min / max	masa jednostki	numer artykułu
RF/2-125S	480 m <sup>3</sup> /h	325 Pa	2 640 rpm	1~230 V	0,38 A	50 W	63 dB(A)	-40 / 70 °C	3,5 kg	43528010
RF/4-125S	260 m <sup>3</sup> /h	85 Pa	1 430 rpm	1~230 V	0,2 A	39 W	46 dB(A)	-40 / 60 °C	3,5 kg	43528015
RF/2-160S	880 m <sup>3</sup> /h	400 Pa	2 700 rpm	1~230 V	0,4 A	101 W	66 dB(A)	-40 / 65 °C	4,0 kg	43528031
RF/2-160S/H	1 220 m <sup>3</sup> /h	518 Pa	2 730 rpm	1~230 V	0,7 A	150 W	65 dB(A)	-40 / 70 °C	4,0 kg	43528033
RF/4-160S	604 m <sup>3</sup> /h	139 Pa	1 425 rpm	1~230 V	0,2 A	39 W	65 dB(A)	-40 / 70 °C	4,0 kg	43528036
RF/4-160S/L	470 m <sup>3</sup> /h	120 Pa	1 412 rpm	1~230 V	0,2 A	34 W	53 dB(A)	-40 / 55 °C	3,3 kg	43528037
RF/2-200S	1 560 m <sup>3</sup> /h	630 Pa	2 762 rpm	1~230 V	1,2 A	271 W	62 dB(A)	-40 / 70 °C	6,9 kg	43528040
RF/4-200S	1 120 m <sup>3</sup> /h	207 Pa	1 400 rpm	1~230 V	0,4 A	99 W	53 dB(A)	-40 / 55 °C	6,4 kg	43528050
RF/4-250S	1 570 m <sup>3</sup> /h	177 Pa	1 430 rpm	1~230 V	0,69 A	132 W	51 dB(A)	-40 / 65 °C	9,0 kg	43528060
RF/4-250T	1 520 m <sup>3</sup> /h	239 Pa	1 400 rpm	3~400 V	0,33 A	139 W	52 dB(A)	-40 / 60 °C	9,0 kg	43528080
RF/6-250S	895 m <sup>3</sup> /h	120 Pa	960 rpm	1~230 V	0,2 A	47 W	42 dB(A)	-40 / 60 °C	9,0 kg	43528100
RF/4-315S	2 430 m <sup>3</sup> /h	219 Pa	1 370 rpm	1~230 V	1,1 A	220 W	55 dB(A)	-40 / 60 °C	10,0 kg	43528070
RF/4-315T	3 300 m <sup>3</sup> /h	290 Pa	1 380 rpm	3~400 V	0,68 A	330 W	58 dB(A)	-40 / 60 °C	11,0 kg	43528090
RF/6-315S	1 750 m <sup>3</sup> /h	131 Pa	950 rpm	1~230 V	0,33 A	70 W	45 dB(A)	-40 / 60 °C	9,5 kg	43528110
RF/4-355S	3 750 m <sup>3</sup> /h	405 Pa	1 398 rpm	1~230 V	2,3 A	540 W	69 dB(A)	-40 / 60 °C	19,0 kg	43528120
RF/4-355T	3 700 m <sup>3</sup> /h	400 Pa	1 352 rpm	3~400Δ V	1,0 A	440 W	67 dB(A)	-40 / 60 °C	19,0 kg	43528125
	3 100 m <sup>3</sup> /h	300 Pa	1 106 rpm	3~400Y V	0,54 A	310 W	62 dB(A)			
RF/6-355T	2 700 m <sup>3</sup> /h	190 Pa	962 rpm	3~400Δ V	0,47 A	180 W	58 dB(A)	-40 / 70 °C	19,0 kg	43528135
	2 200 m <sup>3</sup> /h	150 Pa	807 rpm	3~400Y V	0,2 A	110 W	55 dB(A)			
RF/4-400S	5 000 m <sup>3</sup> /h	330 Pa	1 270 rpm	1~230 V	2,6 A	580 W	70 dB(A)	-40 / 60 °C	23,0 kg	43528140
RF/4-400T	5 000 m <sup>3</sup> /h	500 Pa	1 408 rpm	3~400Δ V	1,3 A	640 W	71 dB(A)	-40 / 70 °C	22,0 kg	43528142
	4 300 m <sup>3</sup> /h	440 Pa	1 140 rpm	3~400Y V	0,8 A	460 W	69 dB(A)			
RF/6-400S	2 900 m <sup>3</sup> /h	210 Pa	931 rpm	1~230 V	0,7 A	180 W	64 dB(A)	-40 / 70 °C	22,0 kg	43528145
RF/6-400T	3 850 m <sup>3</sup> /h	260 Pa	952 rpm	3~400Δ V	0,59 A	270 W	61 dB(A)	-40 / 70 °C	21,0 kg	43528146
	3 300 m <sup>3</sup> /h	170 Pa	690 rpm	3~400Y V	0,3 A	165 W	56 dB(A)			
RF/4-450S	7 700 m <sup>3</sup> /h	700 Pa	1 390 rpm	1~230 V	5,3 A	1 270 W	72 dB(A)	-40 / 60 °C	35,0 kg	43528150
RF/4-450T/L	6 850 m <sup>3</sup> /h	610 Pa	1 388 rpm	3~400Δ V	2,0 A	1 020 W	75 dB(A)	-40 / 70 °C	32,0 kg	43528151
	5 800 m <sup>3</sup> /h	500 Pa	982 rpm	3~400Y V	1,2 A	700 W	71 dB(A)			
RF/4-450T/H	7 400 m <sup>3</sup> /h	440 Pa	1 370 rpm	3~400 V	3,4 A	1 000 W	76 dB(A)	-40 / 60 °C	29,0 kg	43528152
RF/6-450T	4 800 m <sup>3</sup> /h	280 Pa	912 rpm	3~400Δ V	0,8 A	410 W	63 dB(A)	-40 / 80 °C	25,0 kg	43528155
	4 000 m <sup>3</sup> /h	170 Pa	660 rpm	3~400Y V	0,4 A	225 W	60 dB(A)			
RF/4-500T/L	7 800 m <sup>3</sup> /h	690 Pa	1 360 rpm	3~400 V	2,8 A	1 250 W	72 dB(A)	-40 / 60 °C	43,0 kg	43528161
RF/6-500S/L	5 800 m <sup>3</sup> /h	330 Pa	925 rpm	1~230 V	2,2 A	490 W	69 dB(A)	-40 / 60 °C	36,0 kg	43528162
RF/6-500S/H	6 600 m <sup>3</sup> /h	225 Pa	900 rpm	1~230 V	2,5 A	540 W	66 dB(A)	-40 / 60 °C	40,0 kg	43528165
RF/6-500T	5 200 m <sup>3</sup> /h	290 Pa	920 rpm	3~400 V	0,8 A	390 W	65 dB(A)	-40 / 60 °C	36,0 kg	43528164
RF/4-560T/L	13 800 m <sup>3</sup> /h	880 Pa	1 364 rpm	3~400Δ V	4,9 A	2 770 W	75 dB(A)	-40 / 40 °C	55,0 kg	43528170
	11 000 m <sup>3</sup> /h	625 Pa	975 rpm	3~400Y V	2,74 A	1 540 W	68 dB(A)			
RF/4-560T/H	14 600 m <sup>3</sup> /h	640 Pa	1 333 rpm	3~400 V	4,6 A	2 513 W	75 dB(A)	-40 / 45 °C	51,0 kg	43528172
RF/6-560S	9 800 m <sup>3</sup> /h	285 Pa	890 rpm	1~230 V	4,2 A	840 W	65 dB(A)	-40 / 60 °C	48,0 kg	43528174
RF/6-560T	10 000 m <sup>3</sup> /h	400 Pa	966 rpm	3~400Δ V	1,9 A	910 W	68 dB(A)	-40 / 70 °C	48,0 kg	43528176
	8 800 m <sup>3</sup> /h	300 Pa	743 rpm	3~400Y V	1,0 A	570 W	63 dB(A)			
RF/4-630T	21 000 m <sup>3</sup> /h	825 Pa	1 270 rpm	3~400 V	6,6 A	3 900 W	72 dB(A)	-40 / 55 °C	70,0 kg	43528185

\*pomiar wykonany w odległości 1,5m od wylotu, dla Q = 2/3\*Q<sub>max</sub>

\*\* wartość prądu znamionowego może się różnić w zależności od producenta zastosowanego silnika elektrycznego.